



45G TOWER

Part No.	Description	Wt.
45G	10' tower section	70
45AG	9' top section	52
❖ 45AG1	Top Section. Mast support tube is 1-1/4" galv. pipe, threaded on top and projecting 12" above apex of side rails.	60
45AG2	Top Section. Mast support tube is 2-3/8" O.D. tubing, 36" total length, extending 18" above apex of side rails.	60
45AG3	Top Section. Mast support tube is 2-1/4" O.D. tubing, extending 12" above apex of side rails. A 2" O.D. antenna stub will fit snugly inside support tube.	60
45AG4	7' top section. Upper end terminates in flat, triangular plate with 3-1/8" diameter hole in center. Drilled to accept TB3 or TB4 thrust bearing.	52
❖ 45AG5	Top section. Mast support tube is 2-3/4" O.D. and 2-9/16" I.D. tubing, 18" total length.	60
★ 45TG	10' tapered base section (sits on a pier pin - order pier pin separately)	90
★ 45TGIA	10' tapered base section (for use with A4197L base insulator)	114
★ 45TGIA47	10' tapered base section (for use with A4722B base insulator)	114
★ 45RG	10' insulator section for 45G tower (includes 3 # 10470 post insulators)	104
45ACL	10' anti-climb section	165
455ACL3	3 anti-climb metal sheets for attaching to tower section	120
5545G	20' adapter section for joining 45G and 55G sections	160
45JBK	Joint bolt kit	3/4
APL45G	Beacon plate	17
SB45G	5' short base section for use in concrete	35
★ PBC45G	Concrete base plate (sits on pier - order pin separately)	39
★ 3/4X12PP	Pier pin (for BPC45G or 45TG - one required)	1
★ BPH45G	Hinged base plate for concrete	80
★ 5/8X12BB	Concrete base bolt with double nuts (for BPH45G - four required)	1
★ FR45G	Flat roof mount	34
AS455G	Accessory shelf. Triangular plate for mounting most popular Ham rotors. Can be drilled if needed.	8
GA45GD	Guy bracket assembly	23
TB45D	Torque bars (for use with GA45GD guy bracket) (requires 3 shackles, 3/8" maximum size - order separately)	10
3/8S	3/8 shackle	25/100
HBU	Universal house bracket (6" to 30")	15
HBUTVRO	Universal house bracket (18" to 36")	38
TB50	Tower bushing for 45AG top (1-1/4" I.D. x 2" O.D.)	1/2
TB75	Tower bushing for 45AG top (1-1/2" I.D. x 2" O.D.)	1/2
TB3	Heavy duty thrust bearing, recommended for 2" O.D. tubing (fits 45AG4 top section)	2-1/2
TB4	Heavy duty thrust bearing, recommended for 3" O.D. tubing (fits 45AG4 top section)	3
BPL45G	Top plate with guy lugs for mounting AB, TB3 or TB4 bearing	17
SA253UA	Side arm assembly, 2-1/2" to 3' extension, with 2-1/4" support tube	28
TA45	Torque arm stabilizer assembly	56
45TDMKD	Top Dish Mount (knock down)	62
DM45G2	Face dish mount w/2" (2-3/8" O.D.) 5' long standard pipe	52
DM454	Face dish mount w/4" (4-1/2" O.D.) 5' long standard pipe	88
WP45G	Work platform	14
SR245	Safety ring	8
EF2545	Aluminum erection fixture, 12' long (fits all models with 1-1/4" side rails) (Use only to raise one 10' section or any part of a section at one time. Not intended to be used for lifting individuals)	20
P2545	Pole only for EF2545	12
H2545	Head only for EF2545	8

Note: The price on #45 and #5545G sections will be higher on shipments to the following states: Arizona, California, Colorado, Idaho, Montana, Nevada, Oregon, Utah, Washington, and Wyoming.

- ❖ Available by special order only. Allow 60 days for delivery.
- ★ Towers mounted on this base must be bracketed or guyed at all times.
- ◆ This item is not to be used without proper design consideration.

Refer to alphabetical/numerical price list for current prices.