



Broadband Pole Design Properties

120 Ft. AGL Standard Tapered Steel Poles

Physical Properties for 120 Ft. Tapered Steel Poles			
	Light	Medium	Heavy
Design Number	T120LA	T120MA	T120HA
Tip OD, in.	6.50	9.00	12.00
OD @ grade, in.	26.00	28.00	31.00
Butt OD, in.	29.26	31.77	34.95
Number Sides	12	16	18
Δ Dia, in/ft	0.1714	0.1717	0.1717
Side Taper, in/ft	0.0857	0.0857	0.0857
Embedment, ft.	19	22	23
Auger Dia, ft.	3.5	4.0	4.0
Backfill Type	Aggregate	Aggregate	Aggregate
Total Length, ft.	139	142	143
Bare Pole Wt, lbs.	5,538	6,416	8,545
No. of Sections	3	4	4

EPA (ft ³) for 120 Ft. Tapered Steel Poles										
Wind Speed, MPH		Light			Medium			Heavy		
Fastest Mile	3-sec Gust	Sway Limit			Sway Limit			Sway Limit		
		4°	3°	2°	4°	3°	2°	4°	3°	2°
70	85	18	10	—	39	24	6	90	62	35
80	100	18	10	—	36	24	6	80	62	35
90	110	5	5	—	15	15	6	55	55	35
100	120	—	—	—	—	—	—	36	36	35
110	130	—	—	—	—	—	—	23	23	23
120	140	—	—	—	—	—	—	14	14	14

Notes

1. The tabulated EPA values represent the total EPA capacity of the pole. The capacity is based on the assumption that 80% of the total EPA is located at the top of the pole and the remaining 20% is located 20 ft. below the top. When all loading is located at the top of the pole, the tabulated EPA capacity must be reduced by 20%. Refer to *Antenna Index* for the EPA values and sway limitations for specific antenna types.
2. The dash (—) in the table indicates that the pole is not adequate to support antennas for the indicated wind speed.
3. Bare pole weight represents the weight of the pole without accessories.
4. Designs are based on a maximum of (6) ½" internally routed coax per elevation, 90 lbs per elevation for mounts, and antenna weights in pounds equal to 6 times the tabulated EPA values.
5. Pole embedment is based on ANSI/TIA/EIA-222-F normal soil conditions.

Designed By: Man
Date: 7/31/07

Checked By: HA
Date: 7/31/07

Approved By: HA
Date: 7/31/07



Broadband
Pole Design Properties
 120 Ft. AGL Standard Tapered Steel Poles
 Section Data

Section No.	Design Number	Light	Medium	Heavy
		T120LA	T120MA	T120HA
1 (top)	Length, ft.	47.75	25.21	27.71
	Galv. Wt., lbs	1,081	596	844
	Min. Splice, in.	19.0	17.5	26.0
	Max. Splice, in.	25.0	22.5	28.0
2	Length, ft.	48.00	27.96	27.71
	Galv. Wt., lbs	1,852	885	1,073
	Min. Splice, in.	29.0	23.0	32.0
	Max. Splice, in.	37.0	29.5	35.0
3	Length, ft.	48.00	48.00	48.00
	Galv. Wt., lbs	2,605	2,098	2,427
	Min. Splice, in.	—	32.5	37.0
	Max. Splice, in.	—	41.5	47.0
4 (bottom)	Length, ft.	—	48.00	48.00
	Galv. Wt., lbs	—	2,838	4,201
	Min. Splice, in.	—	—	—
	Max. Splice, in.	—	—	—

	Maximum Reactions		
	Light	Medium	Heavy
Download, kips	7.7	9.1	11.5
OTM, ft-kips	405.5	489.5	720.6
Shear, kips	7.1	9.0	11.5

Designed By: Mar
 Date: 7/31/07

Checked By: HA
 Date: 7/31/07

Approved By: HA
 Date: 7/31/07