



## Broadband Pole Design Properties

### 150 Ft. AGL Standard Tapered Steel Poles

Physical Properties for 150 Ft. Tapered Steel Poles			
	Light	Medium	Heavy
Design Number	T150LA	T150MA	T150HA
Tip OD, in.	6.50	9.00	12.00
OD @ grade, in.	31.80	34.30	37.30
Butt OD, in.	36.12	39.00	42.19
Number Sides	12	16	18
Δ Dia, in/ft	0.1802	0.1810	0.1809
Side Taper, in/ft	0.0901	0.0905	0.0905
Embedment, ft.	24	26	27
Auger Dia, ft.	4.0	4.5	5.0
Backfill Type	Aggregate	Aggregate	Aggregate
Total Length, ft.	174	176	177
Bare Pole Wt, lbs.	10,312	12,293	13,961
No. of Sections	4	4	4

EPA (ft <sup>2</sup> ) for 150 Ft. Tapered Steel Poles										
Wind Speed, MPH		Light			Medium			Heavy		
Fastest Mile	3-sec Gust	Sway Limit			Sway Limit			Sway Limit		
		4°	3°	2°	4°	3°	2°	4°	3°	2°
70	85	17	5	—	47	26	6	89	63	31
80	100	17	5	—	47	26	6	89	63	31
90	110	17	5	—	30	26	6	65	63	31
100	120	—	—	—	10	10	6	39	39	31
110	130	—	—	—	—	—	—	22	22	22
120	140	—	—	—	—	—	—	6	6	6

#### Notes

1. The tabulated EPA values represent the total EPA capacity of the pole. The capacity is based on the assumption that 80% of the total EPA is located at the top of the pole and the remaining 20% is located 20 ft. below the top. When all loading is located at the top of the pole, the tabulated EPA capacity must be reduced by 20%. Refer to *Antenna Index* for the EPA values and sway limitations for specific antenna types.
2. The dash (—) in the table indicates that the pole is not adequate to support antennas for the indicated wind speed.
3. Bare pole weight represents the weight of the pole without accessories.
4. Designs are based on a maximum of (6) ½" internally routed coax per elevation, 90 lbs per elevation for mounts, and antenna weights in pounds equal to 6 times the tabulated EPA values.
5. Pole embedment is based on ANSI/TIA/EIA-222-F normal soil conditions.

Designed By: Mar  
Date: 7/31/07

Checked By: HA  
Date: 7/31/07

Approved By: HA  
Date: 7/31/07

7/31/2007

A070102R1-10A



**Broadband**  
**Pole Design Properties**  
 150 Ft. AGL Standard Tapered Steel Poles  
 Section Data

Section No.	Design Number	Light	Medium	Heavy
		T150LA	T150MA	T150HA
1 (top)	Length, ft.	38.17	41.25	43.50
	Galv. Wt., lbs	809	1,114	1,470
	Min. Splice, in.	21.0	26.0	31.0
	Max. Splice, in.	23.0	28.5	34.0
2	Length, ft.	48.00	48.00	48.00
	Galv. Wt., lbs	1,740	2,705	3,155
	Min. Splice, in.	33.0	37.0	42.0
	Max. Splice, in.	36.0	40.5	46.0
3	Length, ft.	48.00	48.00	48.00
	Galv. Wt., lbs	3,371	3,734	4,171
	Min. Splice, in.	44.0	48.0	53.0
	Max. Splice, in.	48.0	52.5	58.0
4 (bottom)	Length, ft.	48.00	48.00	48.00
	Galv. Wt., lbs	4,391	4,740	5,164
	Min. Splice, in.	—	—	—
	Max. Splice, in.	—	—	—

	Maximum Reactions		
	Light	Medium	Heavy
Download, kips	13.3	15.7	17.7
OTM, ft-kips	845.4	995.0	1,153.7
Shear, kips	11.4	14.3	16.0

Designed By: Mar  
 Date: 7/31/07

Checked By: HA  
 Date: 7/31/07

Approved By: HA  
 Date: 7/31/07

7/31/2007

A070102R1-10B